

## Coaxial Cable Connector 24\_MBX-50-2-11/133\_N

### Description

Straight panel bulkhead cable jack, flange mount

Interface standards  
HUBER+SUHNER MBX



### Technical Data

#### Electrical Data

Impedance	50 $\Omega$
Interface frequency max.	6 GHz

#### Mechanical Data

Centre contact	plugged
Outer contact	soldered
Weight	0.005 kg

#### Environmental Data

Operating temperature	-55 °C to 155 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

#### Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	LCP (Liquid crystal polymer)	

### Related Documents

Outline drawing	DOU-00254038
Assembly instruction	DOC-0000447993

### Ordering Information

Bulk 100 pcs package	24_MBX-50-2-11/133_NH
----------------------	-----------------------

### Additional Information

Suitable cables	SUCOFORM_86, MULTIFLEX_86, EZ_86_CU_TP_M17
-----------------	--

### Remarks

Because of the SUCOPLATE body slight discoloration may appear on the solder joint, which has got no influence on the specified technical characteristics of the connector/cable assembly.