

Coaxial Cable Connector 24_MCX-50-2-3/111_N

Description

Straight bulkhead cable feed through

Interface standards

IEC 60169-36_CECC 22220



Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	6 GHz

Mechanical Data

Centre contact	soldered
Outer contact	soldered
Weight	0.0017 kg

Environmental Data

Operating temperature	-55 °C to 155 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	Gold Plating (Nickel underplated)
Body	Brass	Gold Plating (Nickel underplated)
Insulator	PFA / PTFE	
Fastening nut	Brass	Gold Plating (Nickel underplated)
Washer	Bronze	Gold Plating (Nickel underplated)

Related Documents

Outline drawing	DOU-00009837
Catalogue drawing	DCA-00009839
Assembly instruction	DOC-0000389927
Mounting hole	DOU-00008855

Ordering Information

Single package	24_MCX-50-2-3/111_NE
----------------	----------------------

Additional Information

Suitable cables	EZ_86_TP_M17
-----------------	--------------