

## Coaxial Cable Connector 24\_MMCX-50-1-3/111\_O

### Description

Straight bulkhead cable feed through

Interface standards  
SUHNER-MMCX



### Technical Data

#### Electrical Data

Impedance	50 Ω
Interface frequency max.	6 GHz

#### Mechanical Data

Centre contact	crimped
Outer contact	soldered
Weight	0.0009 kg

#### Environmental Data

Operating temperature	-55 °C to 155 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

#### Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	Gold Plating (without Nickel underplating)
Body	Brass	Gold Plating (without Nickel underplating)
Other body part	Brass	Gold Plating (without Nickel underplating)
Insulator	PTFE (Polytetrafluoroethylene)	
Fastening nut	Brass	Gold Plating (without Nickel underplating)

### Related Documents

Outline drawing	DOU-00009293
Assembly instruction	DOC-0000180922
Mounting hole	DOU-00008855

### Ordering Information

Single package	24_MMCX-50-1-3/111_OE
----------------	-----------------------

### Additional Information

Suitable cables	EZ_47_M17, SUCOFORM_47_CU
-----------------	---------------------------