

Coaxial Cable Connector 24_SMA-R50-2-51/133_N

Description

Straight bulkhead cable feed through

Interface standards
SUHNER-SMA-R50



Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	18 GHz

Mechanical Data

Centre contact	crimped
Outer contact	crimped
Weight	0.0034 kg

Environmental Data

Operating temperature	-65 °C to 165 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium / Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Fastening nut	Brass	SUCOPLATE (R) Plating
Washer	Bronze	SUCOPLATE (R) Plating
Crimp ferrule	Copper	SUCOPLATE (R) Plating

Related Documents

Outline drawing	DOU-00009101
Catalogue drawing	DCA-00118188
Assembly instruction	DOC-0000292354
Mounting hole	DOU-00008731

Ordering Information

Single package	24_SMA-R50-2-51/133_NE
----------------	------------------------

Additional Information

Suitable cables	RG_316_/U, ENVIROFLEX_316, RG_188_A/U, RG_174_/U
-----------------	--

Remarks

Reverse polarised interface

Coaxial Cable Connector 24_SMA-R50-2-51/133_N