Electrical Specifications

Frequency:	DC – 18.0 GHz
Impedance	50 Ohms
VSWR:	1.03 + 0.005 x f(GHz)
Insertion Loss:	0.05 x SQT(f(GHz)) dB
RF Leakage:	-(90 – f(GHz)) dB
Insulation Resistance:	shall not be less than 5,000 megohms
Dielectric Withstanding Voltage:	2,500 Volts rms at Sea Level
RF High Potential Withstanding Voltage:	1,500 Volts rms at 5 MHz

Materials

Steel
Corrosion resistant 1.4305 per DIN EN 10088-3 (ASTM-A-582-80)

Copper Beryllium
33-25 CuBe2Pb H per DIN 17666 (ASTM-B-196)

Brass
CuZn39Pb3; CW614N. per DIN EN 12163/12164 (ASTM-B-16)

PTFE
PolyTetraFluoroEthylene per ASTM-D-1710

Silicone Rubber
per DIN 3771 (A-A-59588, Class 2B)
Grade 50-75

Finish

Stainless Steel
shall be passivated per ASTM-A-967

Copper Beryllium
Centre Contacts shall be gold plated to a minimum thickness of .00005 inch (1.27 µm) in accordance with ASTM-B-488, Type III, Code C, Class 1.25

Brass
Ferrules shall be gold plated to a minimum thickness of .000031 inch (0.75 µm) per ASTM-B-488, Type III, Code C, Class 0.75



DRAWING-SETS

3015-11M1-02

THIS DRAWING EMBODIES A CONFIDENTAL PROPERTY DESIGN ORIGINATED BY SPECTRUM ELEKTROTECHNIK GMBH AND ALL DESIGN, MANUFACTURING AND REPRODUCTION, USE AND SALE RIGHTS REGARDING THE SAME ARE EXPRESSLY RESERVED. IT IS SUBMITTED UNDER CONFIDENTIAL RELATIONSHIP FOR A SPECIFIED PURPOSE AND THE RECIPIENT AGREES BY ACCEPTING THIS DRAWING NOT TO SUPPLY OR DISCLOSE ANY INFORMATION REGARDING IT TO ANY UNAUTHORIZED PERSON TO INCORPORATE IN OTHER PROJECTS ANY SPECIAL FEATURES PECULIAR TO THIS DESIGN, ALL PATENT RIGHTS HERETO ARE EXPRESSLY RESERVED BY SPECTRUM ELEKTROTECHNIK GMBH.

STATE	CHANGES	DATE	NAME

SURFACE TREATMENT

ADM. TOL.

SURFACE

	DATE	NAME
DRAWN	18.12.14	Eysoldt
APPROV.		
NORM		

Spectrum Elektrotechnik GmbH

CODE: C3117

SCALE

WEIGHT

MATERIAL

DESCRIPTION N Male Connector straight with metric thread M16x1 to fit on Cable Type EACON 4C

DRAWING NUMBER 3015-11M1-02

SHEET

EDV-NR. KUZ

OF