

2-way reactive power splitter 5502.41.0050

Reactive Splitter

Description

This 2-way power splitters have been designed to evenly split high power signals operating in cellular and 2.4 GHz WiFi bands with minimal reflections or loss. All joints are moisture sealed with O-rings to meet IP67.

The mechanical shape allows easy attachment to wall using the supplied clips. The wide frequency range allows use with multiband antennas and leaky cable systems. With few solder joints and an air dielectric, the loss has been minimized and reliability enhanced.



Technical Data

Electrical Data

	Signal Band 1	Signal Band 2
Frequency	0.694 - 2.5 GHz	2.5 - 3.8 GHz
Return Loss input port	20 dB	20 dB
Splitter Loss	3 dB	3 dB
Insertion Loss	0.1 dB	0.2 dB
Max. Composite Power	500 W	500 W
Intermodulation distortion	-161 dBc	-161 dBc
@ 2 x Carrier Power	43 dBm	43 dBm
	Input 1	
Connector Type	7/16	
Connector Gender	jack (female)	
	Output 1	Output 2
Connector Type	7/16	7/16
Connector Gender	jack (female)	jack (female)
Char. impedance	50 Ω	

Mechanical Data

Dimensions 28.5 x 28.5 x 190 mm (Height x Width x Length)
Weight 0.29 kg

Environmental Data

Environmental conditions indoor/outdoor
Operation temperature -35 °C to 85 °C
Storage temperature -35 °C to 85 °C
Transport temperature -35 °C to 85 °C
IP rating IP67
2011/65/EU (RoHS - including 2015/863 and 2017/2102) compliant

Material Data

Piece Parts	Material	Surface Plating
-------------	----------	-----------------

Related Documents

Outline drawing DOU-00289339
3D-model (Step) DOC-0000689977

2-way reactive power splitter 5502.41.0050