

2-Way Low-loss Power Splitter 92210012

Reactive Splitter

Description

Installation Equipment for Special Communication Antennas:
2-Way Low-loss Power Splitter
Multi-band with 4.3-10 Connector
For indoor and outdoor use



Technical Data

Electrical Data

	Signal Band 1	
Frequency	0.35 - 3.8 GHz	
Insertion Loss	0.05 dB	
Max. Composite Power	300 W	
	Input 1	
Connector Type	4.3-10	
Connector Gender	jack (female)	
	Output 1	Output 2
Connector Type	4.3-10	4.3-10
Connector Gender	jack (female)	jack (female)
Char. impedance	50 Ω	

Mechanical Data

Dimensions	52.5 x 393.3 x 63.5 mm (Height x Width x Length)
Weight	0.964 kg

Environmental Data

Environmental conditions	indoor/outdoor
Operation temperature	-30 °C to 65 °C
IP rating	IP65
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant
WEEE 2002/96/EC	no special marking needed

Material Data

Piece Parts	Material	Surface Plating
-------------	----------	-----------------

Related Documents

Security instruction	DOC-0000278984
----------------------	----------------

2-Way Low-loss Power Splitter
92210012

Mounting material (order separately)

Type	Description	Remarks
92210015	Mounting kit	
734365	1 clamp	Mast: 45–125 mm diameter

