



## Summary

[Request a quote](#)

[Catalog](#)

Coax	1
Plug	Plug - Straight
Locking system	Push-pull
Jacket cable outside diameter [mm]	0.00 - 0.00 mm
Series	00 - NIM-CAMAC

## Technical details

### Electrical Configuration

Coax	1
Contact Termination Coax	Solder
R (max)	6.1 mOhm
Insert configuration value	00.250/50 - 1 Coax (50 Ohm resistor)
Insulator	T: PTFE
Rated current	4 Amps
Impedance	50 Ohm
VSWR	$1.09 + 0.11 * f/\text{GHz}$
Vtest	2100 V (AC), 3000 V (DC)
Contact Type	Coaxial 50 Ohm (Solder)
Test voltage	2.1 kV (rms)
Bucket Dia.	0.6 mm (0.024in)
Contact Dia.	0.7 mm (0.028in)

[https://www.lemo.com/int\\_en/solutions/specialties/00-nim-camac/frt-00-250-nta50.html](https://www.lemo.com/int_en/solutions/specialties/00-nim-camac/frt-00-250-nta50.html)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

## Form & Material

Shell style / Model id	FRT - Straight plug with resistor or shorted
Plug	Straight
Housing material	Brass (nickel plated [SAE AMS QQ N 290]) shell, collet nut, latch sleeve and mid pieces
Locking system	Push-pull
Keying	Circular, male
Weight	4.43 g


## Environment

Environmental protection	IP50
Minimal temperature	-55°C / +260°C
F ret (min)	100 N
Salt Spray Corrosion	>144 hr

## Cable fixation

Cable termination protection	Standard back nut (no additional protection)
Fixation type	Cable collet

## Drawings



## Dimensions

	A	L
mm.	6.4	33
in.	0.25	1.3

[https://www.lemo.com/int\\_en/solutions/specialties/00-nim-camac/frt-00-250-nta50.html](https://www.lemo.com/int_en/solutions/specialties/00-nim-camac/frt-00-250-nta50.html)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

# Recommended By Lemo

Accessories

---

Tools

---

[https://www.lemo.com/int\\_en/solutions/specialties/00-nim-camac/frt-00-250-nta50.html](https://www.lemo.com/int_en/solutions/specialties/00-nim-camac/frt-00-250-nta50.html)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.